


## Arrento Core 600x900x20



Available in a variety of sizes, Arrento® Core porcelain paving is cut to a precise size during production so all tiles are identical, giving you perfect clean lines for a modern aesthetic. The Porcelain Collection from Marshalls is very practical, easy to clean and is slip resistant, even in wet conditions.

### DESCRIPTION

Manufacturing Process	Pressed, glazed, digital printed, kiln fired and rectified porcelain tiles
Base Raw Material	Clay, Feldspar, sand and glaze
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 14411 : 2016
UKCA Marking/DOP	<a href="http://www.marshalls.co.uk/declarations">www.marshalls.co.uk/declarations</a>



## Arrento Core 600x900x20

### PHYSICAL PROPERTIES

Work Dimensions (mm)	600 x 900 x 20
Nominal Dimensions (mm)	600 x 900 x 20
Durability (Freeze-thaw)	Frost resistant - Pass
Slip Resistance (Dry)	82
Slip Resistance (Wet)	72
Transverse/Flexural Split/Breaking	≥ 35 N/mm <sup>2</sup>
Water Absorption (%)	≤ 0.5% by mass as a mean

### SPECIFICATION

Approx unit weight (kg)	24
Reaction to fire	Class A1 - without testing (see decision 96/603/EC, as amended)
Installation	Available on request Keep all units dry before laying & protect incomplete workings during adverse weather or freezing conditions
Dangerous Substances	Lead NPD, Cadmium NPD
Suitability	Domestic use only
<b>SUPPLY</b>	
Av. Pack Size m <sup>2</sup>	24.3
Units Per Pack	45
Av. pack weight (kg)	1080

### FURTHER INFORMATION

Cleaning & Maintenance	Available on request
Weathering	Due to the nature of the product scratch marks may appear on the surface during transportation and handling. If such marks appear they will weather away due to the through colour nature of the product. Weathering It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.
Product Evolution	Marshalls reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice
Contact Us	For technical information on the design, specification and construction when utilising the product, contact Group Technical Services on 0370 411 2234