

Firedstone® Paving 600 x 600 x 38mm



Firedstone -
Autumn



Firedstone -
Dusk



Firedstone -
York

Firedstone® is a stylish and versatile handmade paving cast from original flame treated Yorkstone flags. With an attractive natural colour palette, soft mason fettled edges and lightly textured surface, Firedstone® will bring an authentic natural stone look to your patio.

With its consistent textured finish Firedstone® paving is the ideal choice for family friendly gardens owing to its excellent non-slip properties and low maintenance. Designed to brighten and enhance even the shadiest of garden spaces, Firedstone® is available in four traditional and popular colours.

To complete the look, why not pair our Firedstone® paving with Marshalls Hewnstone edging range to create a path or border? Or to build the ultimate family garden, use Always Green® Playing Field as a hardwearing alternative to a natural lawn.

DESCRIPTION	
Appearance	Solid unit with riven profile surface
Manufacturing Process	Wet cast moulded & vibrated concrete
Base Raw Material	Pigmented concrete
Governing Manufacturing Standards	In-House Company Specification



Firedstone® Paving 600 x 600 x 38mm

PHYSICAL PROPERTIES

Work Dimensions (mm)	595 x 595 x 38
Nominal Dimensions (mm)	600 x 600 x 38
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test)
Durability (Freeze-thaw)	Frost resistant. However may be susceptible to the direct use of de-icing salts or chlorine based products
Material Density	2300 kg/m ³ (typically)
Slip/Skid Resistance (polished)	PSRV > 45
Slip/Skid Resistance (unpolished)	USRV > 45
Water Absorption (%)	≤ 6% by mass as a mean

FURTHER INFORMATION

Cleaning & Maintenance	Available on request
Efflorescence	Any product containing cement during its early life may exhibit a temporary white discolouration known as efflorescence. This is not a product fault and will gradually disappear with exposure to natural weathering and trafficking
Weathering	It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.
Product Evolution	Marshalls reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice
Contact Us	For technical information on the design, specification and construction when utilising the product, contact Group Technical Services on 0370 411 2233

SPECIFICATION

Approx unit weight (kg)	35.5
Emission of Asbestos	No content
External Fire Performance	Deemed to satisfy when used for roofing
Reaction to fire	Class A1 when used for internal flooring
Installation	Available on request. Keep all units dry before laying & protect incomplete workings during adverse weather or freezing conditions

SUSTAINABILITY

Carbon Footprint	14
Suitability	Domestic use only

SUPPLY

Av. Pack Size m ²	7.9
Av. pack weight (kg)	688.16