

Heritage® Paving 450 x 450 x 38mm



British made Heritage® paving is cast from split stone flags with classic mason fettled edges. Versatile and elegant, Heritage offers a popular and attractive riven paving choice with all the charm of genuine newly quarried Yorkstone. Designed to complement every garden space, Heritage paving is available in four replica natural stone colours and five sizes to create a multitude of traditional and contemporary patterns.

If you are looking for your garden transformation to be installed by a professional, find out why you should consider using a Marshall's Registered Installer to complete your transformation and give you complete peace of mind.

To create the perfect traditional garden setting, Marshall's Heritage® combines effortlessly with Marshallite® Pitched Walling and the whole project can be finished off with matching Heritage® Copings. To see how to build a simple garden wall with Marshallite, why not view our how to build a garden wall video.

DESCRIPTION	
Manufacturing Process	Wet cast moulded & vibrated concrete
Base Raw Material	Concrete
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 1339 : 2003

Heritage® Paving 450 x 450 x 38mm

PHYSICAL PROPERTIES

Work Dimensions (mm)	445 x 445 x 38
Nominal Dimensions (mm)	450 x 450 x 38
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test)
Durability (Freeze-thaw)	Frost resistant. However may be susceptible to the direct use of de-icing salts or chlorine based products
Material Density	2300 kg/m ³ (typically)
Slip/Skid Resistance (polished)	PSRV > 45
Slip/Skid Resistance (unpolished)	USRV > 45

SPECIFICATION

Approx unit weight (kg)	20
Emission of Asbestos	No content
External Fire Performance	Deemed to satisfy when used for roofing
Reaction to fire	Class A1 when used for internal flooring

SUSTAINABILITY

Breeam	NA
Carbon Footprint	14
Suitability	Domestic use only

SUPPLY

Av. Pack Size m2	8.9
Av. pack weight (kg)	775.5

FURTHER INFORMATION

Cleaning & Maintenance	Available on request
Efflorescence	Any product containing cement during its early life may exhibit a temporary white discolouration known as efflorescence. This is not a product fault and will gradually disappear with exposure to natural weathering and trafficking
Weathering	It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.
Product Evolution	Marshall's reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice
Contact Us	For technical information on the design, specification and construction when utilising the product, contact Group Technical Services on 0370 411 2233