

Heritage® Paving 600 x 450 x 38mm



British made Heritage® paving is cast from split stone flags with classic mason fettled edges. Versatile and elegant, Heritage offers a popular and attractive riven paving choice with all the charm of genuine newly quarried Yorkstone. Designed to complement every garden space, Heritage paving is available in four replica natural stone colours and five sizes to create a multitude of traditional and contemporary patterns.

If you are looking for your garden transformation to be installed by a professional, find out why you should consider using a Marshalls Registered Installer to complete your transformation and give you complete peace of mind.

To create the perfect traditional garden setting, Marshalls Heritage® combines effortlessly with Marshallite® Pitched Walling and the whole project can be finished off with matching Heritage® Copings. To see how to build a simple garden wall with Marshallite, why not view our how to build a garden wall video.

DESCRIPTION	
Manufacturing Process	Wet cast moulded & vibrated concrete
Base Raw Material	Concrete
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 1339 : 2003



Heritage® Paving 600 x 450 x 38mm

PHYSICAL PROPERTIES		FURTHER INFORMATION	
Work Dimensions (mm)	595 x 445 x 38	Cleaning & Maintenance	Available on request
Nominal Dimensions (mm)	600 x 450 x 38	Efflorescence	Any product containing cement during its early life may exhibit a temporary white discolouration known as efflorescence. This is not a product fault and will gradually disappear with exposure to natural weathering and trafficking
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test)	Weathering	It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.
Durability (Freeze-thaw)	Frost resistant. However may be susceptible to the direct use of de-icing salts or chlorine based products	Product Evolution	Marshalls reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice
Material Density	2300 kg/m ³ (typically)	Contact Us	For technical information on the design, specification and construction when utilising the product, contact Group Technical Services on 0370 411 2233
Slip/Skid Resistance (polished)	PSRV > 45		
Slip/Skid Resistance (unpolished)	USRV > 45		
SPECIFICATION			
Approx unit weight (kg)	27		
Emission of Asbestos	No content		
External Fire Performance	Deemed to satisfy when used for roofing		
Reaction to fire	Class A1 when used for internal flooring		
SUSTAINABILITY			
Carbon Footprint	14		
Suitability	Domestic use only		
SUPPLY			
Av. Pack Size m ²	5.9		
Av. pack weight (kg)	501.6		