

W: www.marshalls.co.uk/commercial Date Created: 09/12/25

E: grouptechnicalservices@marshalls.co.uk

T: 01422 312000

Modal X Smooth Project Pack (8.96m2)

Marshalls

Creating Better Spaces





Modal X® Smooth is a high-quality natural granite alternative to transform your driveway with style and endurance. Available in four exquisite colours; bold charcoal for a statement piece, inviting Oatmeal for a warm ambience, the modern and fresh Light Granite & the cool sophistication of Silver Grey. Available in our most popular plan sizes of 200x100mm, 300x150mm and our traditional project pack, giving you endless possibilities for unique and modern layouts.

Also available in textured finish and a permeable textured option.

DESCRIPTION	
Manufacturing Process	Hydraulically pressed concrete
Base Raw Material	Concrete
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 1338 : 2003
UKCA Marking/DOP	www marshalls co uk/declarations



Date Created: 09/12/25



ः

Marshalls

Creating Better Spaces

PHYSICAL PROPERTIES	
Work Dimensions (mm)	239x159 159x159 79x159
Nominal Dimensions (mm)	240x160x50 / 160x160x50 / 80x160x50
Abrasion Resistance (mm)	≤ 19.2mm (Wide Wheel Abrasion Test)
Material Density	2278kg/m³ (typically)
Slip/Skid Resistance (polished)	PSRV>45
Slip/Skid Resistance (unpolished)	PSRV>45
Transverse/Flexural Split/Breaking	Characteristic tensile splitting strength not less than 3.6MPa. None of the individual results shall be less than 2.9MPa, nor have a failure load less than 250N/mm of splitting length
SPECIFICATION	
Approx unit weight (kg)	1075
External Fire Performance	Deemed to satisfy when used for roofing
Reaction to fire	Class A1 when used for internal flooring
Reaction to fire	
SUPPLY	flooring

A '1 11
Available on request
Any product containing cement during its early life may exhibit a temporary white discolouration known as efflorescence. This is not a product fault and will gradually disappear with exposure to natural weathering and trafficking
It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.
Marshalls reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice