

## Savanna® 160 x 160 x 50mm



Designed to create a classic driveway look and finish, with hardwearing performance, Savanna® combines high quality with great value. These classic shape blocks are available in a range of contemporary colours and sizes to provide the right aesthetic for every property style. Complete the look and add that ideal finishing touch to complete your driveway installation with our matching Drivesett Savanna® Kerb.

To find out more information on how to install a block paved driveway, please see our helpful installation video. Alternatively, if you are looking for a professional to install your driveway, look no further than the Marshall's Register of Accredited Installers.

Complete your driveway project using Marshall's Joint Filling Sand; a special kiln dried sand suitable for use with all types of block paving and available in two colours - Red and Golden.

DESCRIPTION	
Manufacturing Process	Semi dry pressed & vibrated concrete
Base Raw Material	Concrete
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 1338 : 2003
UKCA Marking/DOP	<a href="http://www.marshalls.co.uk/dop">www.marshalls.co.uk/dop</a>



## Savanna® 160 x 160 x 50mm

### PHYSICAL PROPERTIES

Work Dimensions (mm)	158 x 158 x 50
Nominal Dimensions (mm)	160 x 160 x 50
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test)
Material Density	2300 kg/m³ (typically)
Slip/Skid Resistance (polished)	PSRV > 45
Slip/Skid Resistance (unpolished)	USRV > 45
Transverse/Flexural Split/Breaking	Characteristic tensile splitting strength not less than 3.6MPa. None of the individual results shall be less than 2.9MPa, nor have a failure load less than 250N/mm of splitting length

### SPECIFICATION

Approx unit weight (kg)	3
Emission of Asbestos	No content
External Fire Performance	Deemed to satisfy when used for roofing
Reaction to fire	Class A1 when used for internal flooring

### SUSTAINABILITY

Carbon Footprint	20
------------------	----

### SUPPLY

Av. Pack Size m2	10.75
Units Per Pack	420
Av. pack weight (kg)	1244.85

### FURTHER INFORMATION

Cleaning & Maintenance	Available on request
Efflorescence	Any product containing cement during its early life may exhibit a temporary white discolouration known as efflorescence. This is not a product fault and will gradually disappear with exposure to natural weathering and trafficking
Weathering	It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.
Product Evolution	Marshall's reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice
Contact Us	For technical information on the design, specification and construction when utilising the product, contact Group Technical Services on 0370 411 2233

