

Saxon® Paving 450 x 450 x 35mm



Marshall's Saxon® paving combines the functionality and durability of concrete paving with a distinctive and hardwearing textured finish. Using a blend of Yorkstone aggregate the practical, textured non-slip surface of Saxon® is a popular choice with families UK wide.

Available in two popular colours and four sizes, design opportunities with Saxon are limitless and projects created using Saxon often stand the test of time.

For the perfect complementary walling option, Marshall's recommends you consider Marshalite Pitched or Splitface walling. Matching Saxon® edging and Saxon® copings are also available for a cohesive completed project.

If you are looking to install the patio yourself, why not read our helpful How to Lay a Patio guide to give you helpful hints and tips before you start your project.

DESCRIPTION	
Manufacturing Process	Hydraulically pressed concrete
Base Raw Material	Concrete
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 1339 : 2003
UKCA Marking/DOP	www.marshalls.co.uk/dop



Saxon® Paving 450 x 450 x 35mm

PHYSICAL PROPERTIES

Work Dimensions (mm)	448 x 448 x 35
Nominal Dimensions (mm)	450 x 450 x 35
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test)
Material Density	2300 kg/m³ (typically)
Slip/Skid Resistance (polished)	PSRV > 45
Slip/Skid Resistance (unpolished)	USRV > 45
Thermal Conductivity (K value)	Design data as defined in BS EN 13369 : 2004
Transverse/Flexural Split/Breaking	Characteristic bending strength of 3.5 MPa with no individual result less than 2.8 MPa

SPECIFICATION

Approx unit weight (kg)	16.3
Emission of Asbestos	No content
External Fire Performance	Deemed to satisfy when used for roofing
Reaction to fire	Class A1 when used for internal flooring

SUSTAINABILITY

Carbon Footprint	11
------------------	----

SITE WORKS

Coverage	4.9
----------	-----

SUPPLY

Av. Pack Size m2	12.2
Units Per Pack	60
Av. pack weight (kg)	992.4

FURTHER INFORMATION

Cleaning & Maintenance	Available on request
Efflorescence	Any product containing cement during its early life may exhibit a temporary white discolouration known as efflorescence. This is not a product fault and will gradually disappear with exposure to natural weathering and trafficking
Weathering	It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.
Product Evolution	Marshall's reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice
Contact Us	For technical information on the design, specification and construction when utilising the product, contact Group Technical Services on 0370 411 2233

