

Saxon® Coping/Edging 600 x 136 x 50mm



Available in two popular sizes, Marshalls Saxon Coping is ideal to cap your garden walls. This practical coping has been designed using a blend of Yorkstone aggregates to give you the look at feel of a stunning natural stone coping, with all of the inherent strength of engineered concrete.

Achieve a cohesive and co-ordinated garden space with Saxon® paving and edging to match.

DESCRIPTION

Appearance	Solid unit with textured surface
Manufacturing Process	Hydraulically pressed concrete
Base Raw Material	Concrete
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 1339 : 2003





Saxon® Coping/Edging 600 x 136 x 50mm

PHYSICAL PROPERTIES

Work Dimensions (mm)	298 x 134 x 50
Nominal Dimensions (mm)	600 x 136 x 50
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test)
Material Density	2300 kg/m ³ (typically)
Slip/Skid Resistance (polished)	PSRV > 45
Slip/Skid Resistance (unpolished)	USRV > 45
Transverse/Flexural Split/Breaking	Characteristic bending strength of 4.0 MPa with no individual result less than 3.2 MPa

FURTHER INFORMATION

Cleaning & Maintenance	Available on request
Efflorescence	Any product containing cement during its early life may exhibit a temporary white discolouration known as efflorescence. This is not a product fault and will gradually disappear with exposure to natural weathering and trafficking
Weathering	It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.
Product Evolution	Marshalls reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice

SPECIFICATION

Approx unit weight (kg)	11
Emission of Asbestos	No content
External Fire Performance	Deemed to satisfy
Reaction to fire	Class A1
Installation	Available on request Keep all units dry before laying & protect incomplete workings during adverse weather or freezing conditions

Contact Us

For technical information on the design, specification and construction when utilising the product, contact Group Technical Services on 0370 411 2233

SUSTAINABILITY

Carbon Footprint	2.2
------------------	-----

SUPPLY

Av. Pack Size m ²	4.08
Av. pack weight (kg)	469

