

## Saxon® Coping/Edging 600 x 136 x 50mm



Saxon edging provides and effortless finish to any garden space. Blend seamlessly with our classic Saxon paving or create contrast by using Saxon Edging alongside any of the Marshalls paving range. Garden edging isn't just an aesthetically pleasing finishing touch – it also helps to maintain the integrity and strength of the paving it surrounds, protecting your investment for years to come.

Explore our entire kerbs and edgings range for some inspirational design ideas today.

For help with installation of this edging, please refer to our installation guide.

### DESCRIPTION

Appearance	Solid unit with textured surface
Manufacturing Process	Hydraulically pressed concrete
Base Raw Material	Concrete
Governing Manufacturing Standards	In-House Company Specification
UKCA Marking/DOP	<a href="http://www.marshalls.co.uk/dop">www.marshalls.co.uk/dop</a>



# Saxon® Coping/Edging 600 x 136 x 50mm

PHYSICAL PROPERTIES		FURTHER INFORMATION	
Work Dimensions (mm)	598 x 134 x 50	Cleaning & Maintenance	Available on request
Nominal Dimensions (mm)	600 x 136 x 50	Efflorescence	Any product containing cement during its early life may exhibit a temporary white discolouration known as efflorescence. This is not a product fault and will gradually disappear with exposure to natural weathering and trafficking
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test)	Weathering	It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.
Material Density	2300 kg/m <sup>3</sup> (typically)	Product Evolution	Marshalls reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice
Slip/Skid Resistance (polished)	PSRV > 45	Contact Us	For technical information on the design, specification and construction when utilising the product, contact Group Technical Services on 0370 411 2233
Slip/Skid Resistance (unpolished)	USRV > 45		
Transverse/Flexural Split/Breaking	Characteristic bending strength of 4.0 MPa with no individual result less than 3.2 MPa		
SPECIFICATION			
Approx unit weight (kg)	10.6		
Emission of Asbestos	No content		
External Fire Performance	Deemed to satisfy when used for roofing		
Reaction to fire	Class A1 when used for internal flooring		
Installation	Available on request Keep all units dry before laying & protect incomplete workings during adverse weather or freezing conditions		
SUSTAINABILITY			
Carbon Footprint	2.2		
SUPPLY			
Av. pack weight (kg)	469		


 Fair Tax  
 accredited
