

Landscape House, Premier Way, Lowfields Business Park, Elland HX5 9HT Tel: 0333 000 20 50 www.marshalls.co.uk/commercial

T: 01422 312000 F: 01422 312943 E: advisoryservices@marshalls.co.uk

Cromwell Riven

Date Created: 10/05/18





*It should be noted that colour variations and markings are characteristic of Natural Stone. Inherent variations cannot be controlled nor the precise shade of stone guaranteed.

With over 120 years of use in the UK, Cromwell Riven is Marshalls' oldest Yorkstone. A predominantly light buff stone with occasional dark banding, Cromwell is highly sought after for the most prestigious projects. It can be seen in high-profile locations including Kensington High Street and the London Olympic Park.

Its proven performance is a result of its characteristic strength and excellent slip resistance that makes it an ideal choice for any setting. Extremely durable and hard-wearing, it is suitable for both pedestrian and vehicular trafficked areas.

Cromwell Yorkstone is available as paving, setts and tactile. Kerbs and other specials may be available on request.

Produced to the highest standards, both the Cromwell quarry and the manufacturing works are accredited to ISO9001 standards, as well as being ISO14001 Environmentally accredited and OHSAS 18001 Health & Safety accredited.

All Marshalls Yorkstones are fully tested to the appropriate standards

DESCRIPTION	
Appearance	A mainly plain light buff stone with very occasional dark banding
Manufacturing Process	Sawn
Quarry of Origin	Halifax, West Yorkshire
Base Raw Material	Yorkstone
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 1341 : 2012, BS EN 1342 : 2012 & BS EN 1343 : 2012
CE Marking/DOP	https://www.marshalls.co.uk/dop/



















Landscape House, Premier Way, Lowfields Business Park, Elland HX5 9HT Tel: 0333 000 20 50 www.marshalls.co.uk/commercial

T: 01422 312000 F: 01422 312943 E: advisoryservices@marshalls.co.uk

Cromwell Riven

Date Created: 10/05/18

and are CE marked in accordance with the latest legislation.

PHYSICAL PROPERTIES

Tolerances on Work Dimensions (mm) Paving Class 1, Setts Class 2, Kerbs Class 2 tolerances to all dimensions as standard

Others by agreement

MANUFACTURING

Materials Control

CE Marked to BS EN 1341 Paving, 1342

Setts, 1343 Kerbs

FURTHER INFORMATION

Contact Us

For technical information on the design, specification and construction when utilising the product, contact the Technical Advisory Services Department

on 0370 411 2233















