

Joint Filling Sand



Marshall's easy-to-use Concrete Block Paving Joint Filling Sand is recommended for use with all types of concrete block paving and clay pavers.

This specially selected kiln-dried joint-filling sand is available in two colour options to complement a range of schemes. Red is a darker option, while Golden can be used to excellent effect with lighter-coloured products.

Red Kiln Dried Sand can cause staining to occur, especially on lighter-coloured materials. This is caused by natural minerals leeching from the sand when it is wet. This is extremely difficult to remove once contaminated. We would advise the use of generic standard "Silver Kiln Dried Sand", when brushing in, to avoid disappointment.

DESCRIPTION	
Base Raw Material	Sand
Type	Specially selected kiln dried joint filling sand for use with all types of concrete block paving
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS 7533-3 : 2005

Joint Filling Sand

PHYSICAL PROPERTIES

SPECIFICATION

Approx unit weight (kg)	25
Emission of Asbestos	No content

SITE WORKS

Coverage	50mm paving 6 - 8 m ² (approx), 60mm paving 4.5 - 6.5 m ² (approx), 80mm paving 3.5 - 5.5 m ² (approx)
----------	--

SUPPLY

Units Per Pack	56
Av. pack weight (kg)	1400
Packaging	Please note that Red Joint Filling sand only has 40 packs per pallet and therefore the Av. Weight per pallet is 1000 kg

FURTHER INFORMATION

Cleaning & Maintenance	Available on request
------------------------	----------------------

Product Evolution	The evolution of new product design is continuous and information is subject to change without notice. Customers should check with the supplier to ensure that they have the latest details
-------------------	---

Contact Us	For technical information on the design, specification and construction when utilising the product, contact Group Technical Services on 0370 411 2233
------------	---