

## MG15 Grid

Date Created: 10/05/18



A special grade of GeoGrid that has been developed with the UK's market-leading grid supplier, Marshall's MG15 Grid provides additional stability within the sub-base of a Priora permeable pavement.

Installed directly over the sub-grade, the profile of the ribs and the shape of the apertures has been specially developed to maximise interlock with Marshall's angular Priora aggregate, confining movement and improving the CBR of the ground by 1%.

This can drive cost from the system, or in situations where excavation depth is an issue (such as city centres), it could make a permeable system a possibility where it wasn't before.

For more installation information, see the specification page or speak to our design team.

### DESCRIPTION

Base Raw Material	Geocomposite
Governing Manufacturing Standards	In-house Company Specification
CE Marking/DOP	<a href="https://www.marshall's.co.uk/dop">https://www.marshall's.co.uk/dop</a>

# MG15 Grid

Date Created: 10/05/18

## PHYSICAL PROPERTIES

Tolerances	Minimum (mm)	Maximum (mm)
Length		
Width		
Thickness		
Material Density	Not Applicable	

## SPECIFICATION

Emission of Asbestos	No content
----------------------	------------

## SUSTAINABILITY

Breem	These units can achieve an "A" rated system when used in conjunction with the correct sub-base components
-------	---

## SUPPLY

Packaging	On a roll
-----------	-----------

## FURTHER INFORMATION

Cleaning & Maintenance	Information regarding the cleaning & maintenance of this product may be obtained on request
------------------------	---

Product Evolution	The evolution of new product design is continuous and information is subject to change without notice. Customers should check with the supplier to ensure that they have the latest details
-------------------	---

Contact Us	For technical information on the design, specification and construction when utilising the product, contact the Technical Advisory Services Department on 0370 411 2233
------------	---

