Landscape House, Premier Way, Lowfields Business Park, Elland HX5 9HT Tel: 0333 000 20 50 www.marshalls.co.uk/commercial

T: 01422 312000 F: 01422 312943 E: advisoryservices@marshalls.co.uk

Fletcher Bank Masonry & Facades

Date Created: 10/05/18





Fletcher Bank is a fine grained stone hailing from a quarry near Ramsbottom, Lancashire. Buff to grey in colouration, Fletcher Bank has been used in all manner of projects across the UK

DESCRIPTION	
Geological Type	Millstone Grit Series, Carboniferous Sandstone
Quarry of Origin	Fletcher Bank Quarry, Lancashire
Base Raw Material	Sandstone
Petrographical Description	Pale grey to pale buff / buff, fine to medium to coarse grained sandstone
CE Marking/DOP	https://www.marshalls.co.uk/dop



Reaction to fire

Landscape House, Premier Way, Lowfields Business Park, Elland HX5 9HT Tel: 0333 000 20 50 www.marshalls.co.uk/commercial

T: 01422 312000 F: 01422 312943 E: advisoryservices@marshalls.co.uk

Fletcher Bank Masonry & Facades

Date Created: 10/05/18

PHYSICAL PROPERTIES	
Durability (Freeze-thaw)	4.4/7.3 MPa (Mean values to EN 12371 : 2006)
Material Density	2310 kg/m³ (typically)
Open Porosity (%)	12.8
Water Absorption (%)	3.6

Class A1

Durability (Freeze-thaw)	4.4/7.3 MPa (Mean values to EN 12371 : 2006)
Material Density	2310 kg/m³ (typically)
Open Porosity (%)	12.8
Water Absorption (%)	3.6
SPECIFICATION	

FURTHER INFORMATION		
Contact Us	For technical information on the design, specification and construction when	
	utilising the product, contact the Technical Advisory Services Department on 0370 411 2233	