

# Speedcheck Concrete Starter Block Ramp System

Date Created: 06/08/18



Traffic Calming - Speed Check - Charcoal

Marshalls' Speedcheck Concrete Starter Block Ramp System acts as a restraint to allow for ramps to be constructed using block paving. It only requires excavation beneath the ramp areas, keeping disruption to a minimum. Two profiles are available, allowing for slopes of 1:10 and 1:15 inclination.

Depending on the direction, the V edge of the block is used to either start or end the ramp, while the domed side is set on top of the hump, allowing for paving to be laid on the table top. The cubic shape is intended for use with flexibly laid concrete block paving, although other materials may be used if your design warrants it.

The size and shape is designed to complement block paving and give an aesthetically pleasing finish, making it particularly suitable for conservation and residential areas. Choose from 3 colour options - Natural, Red and Charcoal.

## DESCRIPTION

Manufacturing Process	Semi dry pressed & vibrated concrete	
Base Raw Material	Concrete	
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 1338 : 2003	
CE Marking/DOP	www.marshalls.co.uk/dop	
NBS Specification	Q24 110	Q24 112
	Q24 113	

# Speedcheck Concrete Starter Block Ramp System

Date Created: 06/08/18

## PHYSICAL PROPERTIES

Work Dimensions (mm) 200 x 200 x 200/220mm

## SPECIFICATION

Emission of Asbestos No content

External Fire Performance Deemed to satisfy. See commission decision 2000/553/ECU

Reaction to fire Class A1, see commission decision 2000/605/EC

## SUSTAINABILITY

Carbon Footprint 11 kg CO2 lin m

## APPLICATION

Suitability Laid in accordance with BS 7533-6 : 1999  
Suitable for pedestrian traffic, motor cars  
& occasional overrun by LGV's

## FURTHER INFORMATION

**Cleaning & Maintenance** Information regarding the cleaning & maintenance of this product may be obtained on request

**Efflorescence** Any product containing cement during its early life may exhibit a temporary white discolouration known as efflorescence. This is not a product fault and will gradually disappear with exposure to natural weathering and trafficking

**Weathering** It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures

**Product Evolution** The evolution of new product design is continuous and information is subject to change without notice. Customers should check with the supplier to ensure that they have the latest details

**Contact Us** For technical information on the design, specification and construction when utilising the product, contact the Technical Advisory Services Department on 0370 411 2233