## Boda Facades

Date Created: 07/02/19





A gentle white to grey sandstone available in a honed finish. Produced to ISO9001 quality assurance standards. All Marshalls Sandstones are fully tested to the appropriate standards in the UK and are all CE marked in accordance with the latest legislation. Products include Rainscreen Cladding, Ashlar and Walling. Other product variants may be available by agreement.

DESCRIPTION	
Geological Type	Sandstone
Quarry of Origin	Sichuan, China
Petrographical Description	Light grey to buff white grey fine to medium grained Sandstone
CE Marking/DOP	https://www.marshalls.co.uk/dop















Landscape House, Premier Way, Lowfields Business Park, Elland HX5 9HT Tel: 03704 11 22 33 https://www.marshalls.co.uk/commercial

T: 01422 312000 F: 01422 312943 E: services.advisory@marshalls.co.uk

## Boda Facades

## Date Created: 07/02/19

PHYSICAL PROPERTIES	
Durability (Freeze-thaw)	7.6/8.1 MPa (Mean values to EN 12371 : 2010)
Material Density	2540
Open Porosity (%)	7.6
Water Absorption (%)	2.6
Resistance To Fixing (mean)	1600

FURTHER INFORMATION
---------------------

Contact Us

For technical information on the design, specification and construction when utilising the product, contact the Technical Advisory Services Department on 0370 411 2233

SPECIFICATION	
Reaction to fire	Class A1
SUSTAINABILITY	
ERI Score	Our Score: 2 Cluster Score: 0.5
	Carbon Footprint (KgCO2 each)
Boda Facades	Available on Request











