


Laurel Bank Facades

Date Created: 07/02/19



Laurel Bank - Honed

With a unique light buff blend, Laurel Bank has a unique aesthetic that could define a project. With beautiful natural veining, and assured technical performance, Laurel Bank is a statement stone sure to make an impact

DESCRIPTION	
Geological Type	Cambrian Sandstone
Quarry of Origin	Kota Region, Rajasthan, India
Petrographical Description	Pale greyish beige with red brown streaks fine to medium grained sandstone
CE Marking/DOP	https://www.marshalls.co.uk/dop

Laurel Bank Facades

Date Created: 07/02/19

PHYSICAL PROPERTIES

Durability (Freeze-thaw)	35.7/31.9 MPa (Mean values to EN 12371 : 2006)
Material Density	2520 kg/m ³ (typically)
Open Porosity (%)	3
Water Absorption (%)	1.31
Resistance To Fixing (mean)	6400

SPECIFICATION

Reaction to fire	Class A1
------------------	----------

SUSTAINABILITY

ERI Score	Our Score: 3.3 Cluster Score: 2.1
	Carbon Footprint (KgCO ₂ each)
Laurel Bank Facades	Available on Request

FURTHER INFORMATION

Contact Us

For technical information on the design, specification and construction when utilising the product, contact the Technical Advisory Services Department on 0370 411 2233

