


Fixed Head Adjustable Paving Pedestal


Date Created: 11/07/19




Pedestals Mf1 22-35mm




Pedestals Mf2 35-55mm




Pedestals Mf3 55-95mm



Pedestals Mf4 95-165mm



Pedestals Mf5 165-235mm



Pedestals Mf6 200-275mm

Marshall's Fixed Head pedestals are used to create level flooring systems on balconies and roofdecks. Integral spacers create a 4mm joint between paving units and the height can be easily adjusted using the threaded core.

Marshall's pedestals are recommended for use on roofdecks where there will be no vehicular access, but have been tested and proven to withstand loads in excess of one tonne.

DESCRIPTION

Base Raw Material

PP Polypropylene



Fixed Head Adjustable Paving Pedestal

Date Created: 11/07/19

PHYSICAL PROPERTIES

NAME	MIN HEIGHT (MM)	MAX HEIGHT (MM)	BASE DIAMETER (MM)	HEAD DIAMETER (MM)
MF1 Fixed Head Adjustable Pedestal	22	35	200	120
MF2 Fixed Head Adjustable Pedestal	35	55	200	120
MF3 Fixed Head Adjustable Pedestal	55	95	200	120
MF4 Fixed Head Adjustable Pedestal	95	165	200	120
MF5 Fixed Head Adjustable Pedestal	165	235	200	120
MF6 Fixed Head Adjustable Pedestal	200	270	200	120

SPECIFICATION

Working Temperature	-40°C – 120°C
Reaction To Fire	Polypropylene is a combustible material
Spacer Tab Thickness	4mm
Compression	2100kg

SUPPLY

Units Per Pack	25
----------------	----

FURTHER INFORMATION

Cleaning & Maintenance	Cleaning & maintenance details are available on request. Resistant to moulds, algae, alkali, bitumen
Contact Us	For technical information on the design, specification and construction when utilising the product, contact the Technical Advisory Services Department on 0370 411 2233

