

Symphony Classic Paving 1200 x 600 x 20mm

Date Created: 24/10/18



SYMPHONY CLASSIC - BLUE

SYMPHONY CLASSIC - BLAUW

Marshall's Vitrified Paving is the ideal surfacing product for balconies and roofdecks, combining elegant, modern aesthetics with low weight and excellent structural performance.

When installed in conjunction with our range of pedestals or stackable support units, Vitrified Paving creates a "floating floor" paving system which can hide services, waterproofing or insulation beneath the surface - leaving you free to concentrate on designing the ideal finish for your balcony project.

The Vitrified range is divided into 4 distinct categories:

SYMPHONY Classic: The broadest range of contemporary sizes and colours

SYMPHONY Natural: A blend of 6 colours which create a softer, more organic aesthetic taking inspiration from the natural environment

SYMPHONY Plank: A linear range of 4 wood-effect finishes

Arrento: A simple, easy to design range of 6 colours available in a single size 600x600 unit

DESCRIPTION

Product Type	Solid unit with imprinted surface
Appearance	Various
Material	Ceramic
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 14411 : 2016



Symphony Classic Paving 1200 x 600 x 20mm

Date Created: 24/10/18

PHYSICAL PROPERTIES

Tolerances	Minimum (mm)	Maximum (mm)
Length	0.02	0.02
Width	0.02	0.02
Thickness	0.05	0.05
Work Dimensions (mm)	1200 x 600 x 20	
Nominal Dimensions (mm)	1200 x 600 x 20	
Tolerances on Work Dimensions (mm)	±1.25% (to a maximum of ±2mm)	
Durability (Freeze-thaw)	Frost resistant - Pass	
Material Density	2300 kg/m ³ (typically)	
Slip/Skid Resistance (polished)	Mean polished skid resistance value (PSRV) : > 45	
Slip/Skid Resistance (unpolished)	Mean unpolished skid resistance value (USRV) : > 45.	

SPECIFICATION

Approx unit weight (kg)	32.7
-------------------------	------

SUSTAINABILITY

Breem	These units can achieve an "A" rated system when used in conjunction with the correct sub-base components
-------	---

APPLICATION

Suitability	Suitable for pedestrian traffic only
-------------	--------------------------------------

SITE WORKS

Coverage	18.72
----------	-------

SUPPLY

Av. pack size (m ²)	18.72
---------------------------------	-------

Units Per Pack	26
----------------	----

Av. pack weight (kg)	850
----------------------	-----

Packaging	All packs are shrinkwrapped onto pallets for fork off-load or crane off-load if necessary. Additional strapping may be necessary if packs are to be crane lifted to significant height. If this is the case care should be taken to ensure that packs are suitably secured.
-----------	---

FURTHER INFORMATION

Cleaning & Maintenance	Cleaning & maintenance details are available on request
------------------------	---

Product Evolution	Marshall's reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice. The evolution of new product design is continuous and information is subject to change without notice. Customers should check with the supplier to ensure that they have the latest details
-------------------	--

Contact Us	For technical information on the design, specification and construction when utilising the product, contact the Technical Advisory Services Department on 0370 411 2233
------------	---

