

Symphony Vitrified Plank Paving 1200 x 300 x 20mm

Date Created: 07/02/19



Symphony Plank -
Oak

Symphony Plank -
Birch

Symphony Plank -
Cherry

Symphony Plank -
Char

Marshall's Vitrified Paving is the ideal surfacing product for balconies and roofdecks, combining elegant, modern aesthetics with low weight and excellent structural performance.

When installed in conjunction with our range of pedestals or stackable support units, Vitrified Paving creates a "floating floor" paving system which can hide services, waterproofing or insulation beneath the surface - leaving you free to concentrate on designing the ideal finish for your balcony project.

The Vitrified range is divided into 4 distinct categories:

SYMPHONY Classic: The broadest range of contemporary sizes and colours

SYMPHONY Natural: A blend of 6 colours which create a softer, more organic aesthetic taking inspiration from the natural environment

SYMPHONY Plank: A linear range of 4 wood-effect finishes

Arrento: A simple, easy to design range of 6 colours available in a single size 600x600 unit

| DESCRIPTION | |
|-----------------------------------|---|
| Product Type | Solid unit with imprinted surface |
| Appearance | Contemporary |
| Manufacturing Process | Moulded & pressed ceramic tile |
| Base Raw Material | Clay |
| Governing Manufacturing Standards | All data where relevant to be established in accordance with BS EN 14411 : 2016 |
| CE Marking/DOP | https://www.marshall's.co.uk/dop |



Symphony Vitrified Plank Paving 1200 x 300 x 20mm

Date Created: 07/02/19

PHYSICAL PROPERTIES

| Tolerances | Minimum (mm) | Maximum (mm) |
|------------------------------------|--|--------------|
| Length | 0.02 | 0.02 |
| Width | 0.02 | 0.02 |
| Thickness | 0.05 | 0.05 |
| Work Dimensions (mm) | 1200 x 300 x 20 | |
| Nominal Dimensions (mm) | 1200 x 300 x 20 | |
| Tolerances on Work Dimensions (mm) | ±1.25% (to a maximum of ±2mm) | |
| Durability (Freeze-thaw) | Frost resistant - Pass | |
| Material Density | 2300 kg/m³ (typically) | |
| Slip/Skid Resistance (polished) | R11 | |
| Slip/Skid Resistance (unpolished) | Mean unpolished skid resistance value (USRV) : > 45. | |
| Water Absorption (%) | 0.5% Maximum | |

SPECIFICATION

| | |
|-------------------------|--|
| Approx unit weight (kg) | 16.3 |
| Emission of Asbestos | No content |
| Reaction to fire | A1FL (WT), see commission decision 96/603/EC |

SUSTAINABILITY

| | |
|------------------|---|
| Breem | These units can achieve an "A" rated system when used in conjunction with the correct sub-base components |
| Carbon Footprint | Available on Request |

APPLICATION

| | |
|-------------|--------------------------------------|
| Suitability | Suitable for pedestrian traffic only |
|-------------|--------------------------------------|

SITE WORKS

| | |
|----------|-------|
| Coverage | 17.28 |
|----------|-------|

SUPPLY

| | |
|----------------------|---|
| Av. pack size (m²) | 17.28 |
| Units Per Pack | 48.00000000000001 |
| Av. pack weight (kg) | 780 |
| Packaging | All packs are shrinkwrapped onto pallets for fork off-load or crane off-load if necessary. Additional strapping may be necessary if packs are to be crane lifted to significant height. If this is the case care should be taken to ensure that packs are suitably secured. |

FURTHER INFORMATION

| | |
|------------------------|--|
| Cleaning & Maintenance | Cleaning & maintenance details are available on request |
| Weathering | It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures. |
| Product Evolution | Marshall's reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice. The evolution of new product design is continuous and information is subject to change without notice. Customers should check with the supplier to ensure that they have the latest details |
| Contact Us | For technical information on the design, specification and construction when utilising the product, contact the Technical Advisory Services Department on 0370 411 2233 |

