Landscape House, Premier Way, Lowfields Business Park, Elland HX5 9HT Tel: 0333 000 20 50 https://www.marshalls.co.uk/commercial

T: 01422 312000 F: 01422 312943

E: services.advisory@marshalls.co.uk

Date Created: 16/01/19

Saxon HB2 Kerb 125 x 255/150 Drop LH Natural





Marshalls Saxon Concrete Kerb is now available in the popular HB2 traditional profile and the best-selling size: 125 x 255mm. Unlike with other kerb products, there's no secondary process to create this slip resistant texture, making this a lower-cost alternative with a rustic and understated aesthetic.

DESCRIPTION	
Appearance	Solid unit with textured surface
Manufacturing Process	Hydraulically pressed concrete
Base Raw Material	Concrete
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 1340 : 2003
CE Marking/DOP	https://www.marshalls.co.uk/dop
NBS Specification	Q10 112 Q10 10 Q10 510













BUSINESS IN THE COMMUNITY













Landscape House, Premier Way, Lowfields Business Park, Elland HX5 9HT Tel: 0333 000 20 50 https://www.marshalls.co.uk/commercial

T: 01422 312000 F: 01422 312943

E: services.advisory@marshalls.co.uk

Date Created: 16/01/19

Saxon HB2 Kerb 125 x 255/150 Drop LH Natural

PHYSICAL PROPERTIES	
Work Dimensions (mm)	125 x 255 x 915
Tolerances on Work Dimensions (mm)	Width ±3mm, height ±3mm, length ±3mm
Abrasion Resistance (mm)	≤ 23mm (Wide Wheel Abrasion Test)
Durability (Freeze-thaw)	≤ 1.0 kg/m² as a mean with no individual value > 1.5 kg/m²
Material Density	2300 kg/m³ (typically)
Slip/Skid Resistance (polished)	Mean polished skid resistance value (PSRV) : > 45
Slip/Skid Resistance (unpolished)	Mean unpolished skid resistance value (USRV) : > 45.

SPECIFICATION	
Approx unit weight (kg)	59
Emission of Asbestos	No content
External Fire Performance	Deemed to satisfy. See commission decision 2000/553/ECU
Reaction to fire	Class A1, see commission decision 2000/605/EC

SUSTAINABILITY		
Carbon Footprint	Available on Request	

SUPPLY	
Units Per Pack	16
FLIDTLIED INFORMATION	N.
FURTHER INFORMATION Cleaning & Maintenance	Cleaning & maintenance details are available on request
Efflorescence	Any product containing cement during its early life may exhibit a temporary white discolouration known as efflorescence. This is not a product fault and will gradually disappear with exposure to natural weathering and trafficking
Weathering	It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.
Product Evolution	The evolution of new product design is continuous and information is subject to change without notice. Customers should check with the supplier to ensure that they have the latest details. Marshalls reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice
Contact Us	For technical information on the design, specification and construction when utilising the product, contact the Technical Advisory Services Department on 0370 411 2233























