







The most popular traditional block paving

Original and popular traditional block paving renowned for its lasting performance, offering a classic, high quality driveway. Designed to create an established, timeworn appearance, with a variety of block sizes and rich, traditional colour blends. With coordinating kerbs, walling and circle features available, Drivesett Tegula Original really is the complete package.

Single Size Packs	Sizes mm (nominal)	No. items/ pack	No/m²	m²/ pack	Colours	Order Select
Large	240 x 160 x 50	284	26	10.91	TR H	
Medium	160 x 160 x 50	426	39	10.91	PG HA A H	
Small	120 x 160 x 50	606	52	11.64		√ *

^{*}Order Select minimum quantity 1m² in single sizes. For details see p194.

Tegula is a trademark of SF Kooperation GmbH.

DRIVESETT® TEGULA® ORIGINAL

Driveways



Traditional (TR)

Pennant Grey (PG)

Hazelnut (HA)

Autumn (A)

Harvest (H)

Complete this look

Steps p166, Kerbs p181, Walling p148, Circle p127, Permeable p142

Visit Marshalls.co.uk/homeowners for more information or to order a sample today









^{*}Project packs available, details on next page.



DRIVESETT® TEGULA® ORIGINAL PROJECT PACK

Driveways



Traditional (TR)

Harvest (H)

Pennant Grey (PG)

Versatile colours for a bespoke finish

Drivesett Tegula Original is available in 9.73m² Project Packs, which contain the perfect proportion of block sizes to achieve a balanced look. Project Packs are ideal for easily calculating the correct number of packs to order with a minimum of waste. Available in the three most popular Drivesett Tegula Original colours.

Project pack will not blend with single size Tegula or accessories, it has been designed to be used alone.

Project Packs	Sizes mm (nominal)	m²/pack	Colours
Large	240 x 160 x 50		TR H PG
Medium	160 x 160 x 50	9.73	
Small	120 x 160 x 50		

Tegula is a trademark of SF Kooperation GmbH.

Complete this look

Steps p166, Kerbs p181, Walling p148

Visit Marshalls.co.uk/homeowners for more information or to order a sample today

All products come with specific installation guidelines. See p191 for additional product notes or contact our technical team on 0370 411 2233.





