Landscape House, Premier Way, Lowfields Business Park, Elland HX5 9HT Tel: 03704 11 22 33 https://www.marshalls.co.uk/commercial

T: 01422 312000 F: 01422 312943

E: services.advisory@marshalls.co.uk

Date Created: 26/07/19

Taksim Granite









*It should be noted that colour variations and markings are characteristic of Natural Stone. Inherent variations cannot be controlled nor the precise shade of stone guaranteed.

Taksim is a hard wearing pink granite suitable for a variety of applications.

DESCRIPTION	
Appearance	A pale pink to pale pink / grey coarse grained granite
Manufacturing Process	Sawn
Geological Type	Granite
Quarry of Origin	Vietnam
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 1341 : 2012, BS EN 1342 : 2012 & BS EN 1343 : 2012
Petrographical Description	A pale pink to pale pink/grey, coarse to very coarse grained granite.
CE Marking/DOP	https://www.marshalls.co.uk/dop















Landscape House, Premier Way, Lowfields Business Park, Elland HX5 9HT Tel: 03704 11 22 33 https://www.marshalls.co.uk/commercial

T: 01422 312000 F: 01422 312943

E: services.advisory@marshalls.co.uk

Date Created: 26/07/19

Taksim Granite

PHYSICAL PROPERTIES					
	Tolerances on Work Dimensions (mm)	Paving Class 1, Setts Class 2, Kerbs Class 2. Tolerances to all dimensions as standard. Others by agreement Others by agreement			
	Abrasion Resistance (mm)	16.5mm (Mean value to EN 14157: 2004)			
	Durability (Freeze-thaw)	13 MPa (Mean value to EN 12372: 2006 (After 56 cycles of Freeze / Thaw to EN 12371: 2010)			
	Material Density	2630 kg/m3 (Mean value to EN 1936: 2006)			
	Open Porosity (%)	0.5% (Mean value to EN 1936: 2006			
	Compressive Strength (MPa)	213 MPa (Mean value to EN 1926: 2006 (LEV = 191 MPa))			
	Water Absorption (%)	0.22% (Mean value to EN 13755: 2008)			
	Transverse/FlexuralSplit/Breaking	13 MPa (Mean value to EN 12372: 2006 (LEV = 11 MPa))			

TEXTURE SPECIFIC PROPERTIES				
	Fine Picked	Flamed	Polished	
Surface Roughness (Rz-µm)	>60	>55		

MANUFACTURING	
Materials Control	CE Marked to EN 1341 (Slabs for Paving), EN 1342 (Setts), EN 1343 (Kerbs)
SUSTAINABILITY	
ERI Score	Our Score: 3.8 Cluster Score: 2.1
Carbon Footprint	Available on Request

FURTHER INFORMATION				
Contact Us	For technical information on the design, specification and construction when utilising the product, contact the Technical Advisory Services Department on 0370 411 2233			















Landscape House, Premier Way, Lowfields Business Park, Elland HX5 9HT Tel: 03704 11 22 33 https://www.marshalls.co.uk/commercial

T: 01422 312000 F: 01422 312943

E: services.advisory@marshalls.co.uk

Date Created: 26/07/19

Taksim Granite

Suggested Plan Sizes















