

## PRODUCT GROUP

Approval No. 2008/34

1. SUPPLIER

**CPM Group Ltd** 

Address:

Mells Road

Mells

Frome

Somerset

**BA11 3PD** 

Telephone No:

01179 814 500

Fax No:

01179 814 511

E-mail:

sales@cpm-group.com

2. PRODUCT

**Concrete Pipe System** 

2.1 Brief Description of Product

**CPM Concrete Drainage Pipes** 

## 2.2 Approval Granted

• CPM Concrete Drainage Pipes of nominal diameter 225mm to 1,800 mm (inclusive) approved for use in stormwater attenuation / storage systems for both combined flows and storm flows in both on and off-line applications except in highways (including estate roads and car parks) where pipes can only be up to 900mm diameter but subject to the limitations described below.

Pipe Component	<u>Diameter</u>
Stop End Bend	900 – 1800mm
Side Entry Manhole	900 – 1800mm
Mid Entry Manhole	900 – 1800mm
Stop End Pipe	900 – 1800mm
End Entry Pipe	1350 – 1800mm

- For off-line stormwater attenuation / storage systems, the manhole diameter may be the same as the pipe diameter subject to a minimum diameter of 1200mm.
- Where third party ancillaries are installed as part of an overall solution e.g. fitting
  Hydrobrakes, CPM Group Ltd will provide a certificate from such third parties
  confirming that all their requirements have been met in the stormwater
  attenuation/storage systems design and that these follow the details agreed with
  Dŵr Cymru Welsh Water.

Approved:

(for DCWW Product Group)

Date:

1 November 2008