

## Conservation X Priora 160 x 160 x 80

Date Created: 13/04/21



Conservation X  
Priora Block - Silver  
Grey

Conservation X  
Priora Block -  
Charcoal

Conservation X  
Priora Block -  
Cream

\*Natural products are manufactured from aggregates sourced locally to the works and contain no pigmentation, therefore colour variation between products from different works is possible.

**Conservation X Priora Block** offers excellent drainage without the need for drainage channels coupled with a striking, contemporary surface option using a blend and mix of natural crystalline aggregates to achieve a granite-look finish. Available in Charcoal and Silver Grey from our Mistral Priora range, and the new Cream.

Marshalls' market-leading Priora system has been proven over 15 years of successfully installed projects. The patented nib on the edge of the blocks creates voids through which water falls into a specially prepared sub-base. The nibs interlock to enhance surface stability, with tests showing they provide 40% more interlock than our standard block. The result is maximum structural integrity as well as unsurpassed SuDS performance. Provided the sub-base is installed to Marshalls' specification, **Conservation X Priora Block** is suitable for all loading requirements. This means specifying Marshalls Priora blocks will bring long-term benefits in relation to pavement longevity and maintenance requirements.

To achieve your full-scheme design; see the full Conservation X range [here](#).

### DESCRIPTION

Appearance	Solid unit with integral spacers intended to create 6mm drainage apertures
Manufacturing Process	Semi dry pressed & vibrated concrete
Base Raw Material	Concrete
Governing Manufacturing Standards	All data where relevant to be established in accordance with BS EN 1338 : 2003
Type	Solid unit with integral spacers intended to create 6mm drainage apertures
CE Marking/DOP	<a href="https://www.marshalls.co.uk/dop">https://www.marshalls.co.uk/dop</a>
NBS Specification	Q24 115

# Conservation X Priora 160 x 160 x 80

Date Created: 13/04/21

## PHYSICAL PROPERTIES

Work Dimensions (mm)	160 x 160 x 80
Nominal Dimensions (mm)	160 x 160 x 80
Tolerances on Work Dimensions (mm)	Length $\pm 2$ mm, width $\pm 2$ mm, thickness $\pm 3$ mm
Abrasion Resistance (mm)	$\leq 23$ mm (Wide Wheel Abrasion Test)
Durability (Freeze-thaw)	$\leq 1.0$ kg/m <sup>2</sup> as a mean with no individual value $> 1.5$ kg/m <sup>2</sup>
Material Density	2300 kg/m <sup>3</sup> (typically)
Slip/Skid Resistance (polished)	Mean polished skid resistance value (PSRV) : $> 45$
Slip/Skid Resistance (unpolished)	Mean unpolished skid resistance value (USRV) : $> 45$ .
Thermal Conductivity (K value)	Design data as defined to BS EN 13369 : 2013
Tensile Splitting Strength	Characteristic tensile splitting strength not less than 3.6 MPa. None of the individual results shall be less than 2.9 MPa, nor have a failure load less than 250N/mm of splitting length

## SPECIFICATION

Approx unit weight (kg)	4.7
Emission of Asbestos	No content
External Fire Performance	Deemed to satisfy when used for roofing
Reaction to fire	Class A1 when used for internal flooring
Materials Control	CE Marked to BS EN 1338 : 2003 Concrete Blocks

## SUSTAINABILITY

Breem	These units can achieve an "A" rated system when used in conjunction with the correct sub-base components
Carbon Footprint	34 kg CO <sub>2</sub> m <sup>2</sup>

## APPLICATION

Suitability	Laid in accordance with BS 7533-3 : 2006
-------------	--

## SITE WORKS

Coverage (m <sup>2</sup> )	7.2
----------------------------	-----

## SUPPLY

Av. pack weight (kg)	1168
Packaging	All packs are shrinkwrapped onto pallets for fork off-load or crane off-load if necessary

## FURTHER INFORMATION

Cleaning & Maintenance	Available on request
Efflorescence	Any product containing cement during its early life may exhibit a temporary white discolouration known as efflorescence. This is not a product fault and will gradually disappear with exposure to natural weathering and trafficking
Weathering	It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.
Product Evolution	The evolution of new product design is continuous and information is subject to change without notice. Customers should check with the supplier to ensure that they have the latest details Product Evolution Marshalls reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice
Contact Us	For technical information on the design, specification and construction when utilising the product, contact Group Technical Services on 0370 411 2233