

## GB Declaration of Performance: SM-125

Marshall's Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. *Unique identification code of the product-type:*

**Dry-pressed ceramic tiles, with water absorption  $E_b < 0.5\%$**

2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Lucent Blue Porcelain**

3. *Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:*

**For Internal and external walls and floorings**

4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Stonemarket, Oxford Road, Ryton-on-Dunsmore, Coventry, Warwickshire, CV8 3EJ**

5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 4**

7. *In case of the declaration of performance concerning a construction product covered by a designated standard:*

**BS EN 14411:2012**

8. *In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:*

**Not applicable**

*9. Declared performance*

| Essential Characteristics              | Performance   | Relevant Clause of BS EN 14411:2012 |                                 |
|--|---|-------------------------------------|---------------------------------|
| <b>Reaction to Fire</b>                | AIFL (WT)<br>Without testing (see Decision 96/603/EC, as amended) | B.14                                |                                 |
| <b>Release of Dangerous Substances</b> | <b>Cadmium</b> NPD  | C.3 a)<br>EN 10545-15               |                                 |
|  | <b>Lead</b> NPD   |                                     |                                 |
| <b>Breaking Strength</b>               | 37.40 MPa   | B.10a<br>EN 12004                   |                                 |
| <b>Slip Resistance</b>                 | <b>Dry</b><br>55  | <b>Wet</b><br>48                    | CEN/TS<br>16165:2012<br>Annex C |
| <b>Tactility</b>                       | NPD   | CEN/TS<br>15209                     |                                 |
| <b>Durability</b>                      | <b>Internal Uses</b><br>Pass                                      | B.8<br>EN10545-12                   |                                 |
|  | <b>External Uses</b><br>Pass                                      |                                     |                                 |

*Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:*

**Not applicable**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom” under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Simon Bourne  
Group Operation Director

Date: 13<sup>th</sup> July 2021

Place of Issue: Elland, Halifax, UK