



Declaration of Performance: SM-165

Marshall's Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

Slabs of Natural Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Namera Desert Blend (50% Elegant Brown, 50% Imperial Grey)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Domestic/Commercial Paving for external uses (see Stonemarket brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Stonemarket, Oxford Road, Ryton-on-Dunsmore, Coventry, Warwickshire, CV8 3EJ

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

BS EN 1342:2012

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

**Declaration of Performance: SM-165**

Marshall's Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

9. Declared performance

Essential Characteristics	Performance		Relevant Clause of BS EN 1342:2012
Petrographic	Denomination: Elegant Brown Grey to pale grey and grey/brown, predominantly fine to very fine grained and occasionally medium grained fresh Limestone, well to very well compacted, generally hard and robust.	Denomination: Imperial Grey Grey to pale grey and grey/brown predominantly fine to very fine grained and occasionally medium grained, fresh Limestone, generally well compacted, hard and robust.	4.1.1
Release of dangerous substances	NPD	NPD	4.11
Compressive Strength Lowest expected Value	72.44 MPa	112MPa	4.4
Slip Resistance (wet value)	67 (mean)	66 (mean)	4.6.1
Skid Resistance	94 (mean)	96 (mean)	4.6.2
Freeze/thaw resistance (general) Before and after 56 cycles	16.6/15.2Mpa	18.1/14.3MPa	4.3.1
Freeze/thaw resistance (De-icing salts)	NPD	NPD	4.3.2
Polishing In Use	NPD	NPD	4.6.3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Rory Kendrick
International Stone Sourcing Director

Date: 17th February 2020
Place of issue: Elland, Halifax, UK