



## GB Declaration of Performance: SM-189

Marshall's Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. *Unique identification code of the product-type:*

**Dry-pressed ceramic tiles, with water absorption Eb<0.5%**

2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Acento Porcelain**

3. *Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:*

**For Internal and external walls and floorings**

4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Stonemarket, Oxford Road, Ryton-on-Dunsmore, Coventry, Warwickshire, CV8 3EJ**

5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 4**

7. *In case of the declaration of performance concerning a construction product covered by a designated standard:*

**BS EN 14411:2012**

8. *In case of the declaration of performance concerning a construction product for which a UK Assessment has been issued:*

**Not applicable**

**GB Declaration of Performance: SM-189**

Marshall's Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

**9. Declared performance**

Essential Characteristics	Performance	Relevant Clause of BS EN 14411:2012
<b>Reaction to Fire</b>	Class A1 Without testing (see Decision 96/603/EC, as amended)	B.14
<b>Release of Dangerous Substances</b>	<b>Cadmium</b> NPD	C.3 a)
	<b>Lead</b> NPD	EN 10545-15
<b>Breaking Strength</b> <b>Thickness &gt; 7,5 mm</b> <b>Thickness &lt; 7,5 mm</b>	>1.300 N >700 N	B-2) EN10545-4
<b>Slip Resistance</b>	R11/C	B9 CEN/TS 16165
<b>Tactility</b>	NPD	B.15 CEN/TS 15209
<b>Bond Strength/Adhesion, only for wall tiles:</b> <b>Cementitious adhesives type C2</b>	>N/mm <sup>2</sup>	B-10 a) EN12004:2007+a1:2012-4.1
<b>Thermal shock resistance</b>	Pass	B6 10545-9
<b>Durability</b>	<b>Internal Uses</b> Pass	B.8 EN 10545-12
	<b>External Uses (Freeze-Thaw Resistance)</b> Pass	B.8 EN 10545-12

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**Not applicable**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom" under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Simon Bourne  
Group Operations Director

Date: 13<sup>th</sup> July 2021

Place of Issue: Elland, Halifax, UK