

PRODUCT SPECIFICATION MATERIAL: RhinoGuard 15-30 Seat Ground Frame - Mild Steel Leg Sleeve - Mild Steel Seat Frame - Stainless Steel, Grade 316 Slats - Hardwood Timber FINISH: RhinoGuard 15-30 Seat Ground Frame - Hot Dip Galvanised Leg Sleeve - Galvanised & Powder Coated Seat Frame - Bead Blasted Slats - Natural / Untreated FIXING TYPE: Root Fixed. APPROX WEIGHT: RhinoGuard 15-30 Seat Ground Frame - 32kg (each) Leg Sleeve - 11kg (each) Seat Top - 40kg STANDARD: IWA 14-1:2013 PERFORMANCE: V1500[M1]/48/90:5.5 FOUNDATIONS: Concrete grade C30-C40 mass fill. Foundation sizes given are suited to sub-soils with good load	A
RhinoGuard 15-30 Seat Ground Frame - Mild Steel Leg Sleeve - Mild Steel Seat Frame - Stainless Steel, Grade 316 Slats - Hardwood Timber FINISH: RhinoGuard 15-30 Seat Ground Frame - Hot Dip Galvanised Leg Sleeve - Galvanised & Powder Coated Seat Frame - Bead Blasted Slats - Natural / Untreated FIXING TYPE: Root Fixed. APPROX WEIGHT: RhinoGuard 15-30 Seat Ground Frame - 32kg (each) Leg Sleeve - 11kg (each) Seat Top - 40kg STANDARD: IWA 14-1:2013 PERFORMANCE: V/1500[M1]/48/90:5.5 FOUNDATIONS: Concrete grade C30-C40 mass fill. Foundation sizes given are suited to sub-soils with good load	A
FIXING TYPE: Root Fixed. APPROX WEIGHT: RhinoGuard 15-30 Seat Ground Frame - 32kg (each) Leg Sleeve - 11kg (each) Seat Top - 40kg STANDARD: IWA 14-1:2013 PERFORMANCE: V/1500[M1]/48/90:5.5 FOUNDATIONS: Concrete grade C30-C40 mass fill. Foundation sizes given are suited to sub-soils with good load	
Concrete grade C30-C40 mass fill. Foundation sizes given are suited to sub-soils with good load	В
 bearing capabilities. Where adverse site conditions are met professional advice to be sought. INSTALLATION: Excavate suitable foundation as shown. Position RhinoGuard 15-30 Ground Frames at specified centres and cast concrete C30 - C40. Allow foundations to cure. Secure Leg Sleeves to the Ground Frames using the M20 Hex Bolts supplied. Provide aurface fraction for the and strong the Lag Sleaves 	С
 5. Reinstate surface finish up to and around the Leg Sleeves. 6. Secure the Seat Top to the Leg Sleeves using M10 fixings supplied. 	D
For operation and maintenance please refer to the Marshalls Street Furniture Maintenance Guide. Unless otherwise stated: All Dimensions are in Millimetres Marshalls PLC reserves the right to change the specifications of any product detailed without prior notice. A IJ Ist Release 01/02/2022	E
Rev Inits Revision Notes ER No. Date Title: RG 15-30 Geo Seat 1.8 316 Root Fixed BB Drawing No: PS-GE-SE-10123 PS-GE-SE-10123 THRO ANGLE PROJECTION Vermier Way, Lowfields Business Park, TEL: 0870 600 2426 EMAIL: mst.sales@marsholls.co.uk	
Marshalls Elland, Halifax, West Yorks, KX5 9HT www.morshalls.co.uk/commercial DRAWN BY: IJ DATE: 01/02/2022 DO NOT SCALE DRAWING REVISION: SCALE: 1:15@A3 SHEET: 1 of 1 7 8	F