

Longfloor Binder Material Safety Data Sheet

This document is prepared in accordance with Annex II of the REACH Regulation EC 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010)

1. Identification of the substance/ preparation and of the company/undertaking

1.1 Identification of the substance or preparation

This datasheet applies to the following products:

1.1.1 Limestone

Substance Name	Longfloor Binder
Synonyms	Longfloor
Chemical Name and Formula	Calcium Carbonate - CaCO ₃ >95% & selected substances
Trade Name	Longfloor
CAS N°	1317-65-3 & 126-30-7
EINECS N°	215-279-6 & 204-781-0
Reach Registration Number	01-2119480 (additive only, Limestone is REACH exempt as a naturally occurring material)

1.2 Use of the substance

Longfloor binder is used in industrial installations to manufacture / formulate a flowing mortar type mixture used in building and construction work as a screed material. Typically EN197-1 Common Cement is added along with a 0-4mm sand complying with BS EN 12620 and water to produce the flowing mortar.

1.3 Company Identification

Name	Longcliffe Quarries Ltd
Address	Brassington Matlock Derbyshire DE4 4HN
Phone	01629 540284
Email	sales@longcliffe.co.uk

1.4 Emergency telephone

UK/European Emergency	999/112
Longcliffe Transport Emergency Contact	01629 540284
Refer to Hospital Accident and Emergency Department	

2. Hazards identification

2.1 Classification of the substance

2.1.1 Classification according to Regulation (EC) 1272/2008

According to Regulation (EC) No 1272/2008 [CLP]
Eye Dam./Irrit.1



Longfloor Binder Material Safety Data Sheet

2.1.2 Classification according to Directive 67/548/EEC

According to Directive 67/548/EEC or 1999/45/EC
Possible Hazards: Risk of serious damage to eyes

2.2 Label elements

Globally Harmonized System, EU (GHS)



Pictogram:

Signal Word: Danger

Hazard Statement: H318 Causes severe eye damage

Precautionary Statements (Prevention): P280 wear eye/face protection

Precautionary Statements (Response): P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do continue rinsing. P310 immediately call a poison centre or doctor/physician.

2.2.1 Labelling according to Regulation (EC) 1272/2008

Signal word: No signal word

Hazard pictogram: No pictogram

Hazard statements: None

Precautionary statements: None

2.2.2 Labelling according to Directive 67/548/EEC



Hazard symbol(s) Xi Irritant

R-phrase(s) R41 Risk of serious damage to eyes

S-phrase(s) S39 Wear eye/face protection. S26 in case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Indication of danger: None

Risk phrases: Not applicable

Safety phrases: S22: Do not breathe dust

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S36: Wear suitable protective clothing

S37: Wear suitable gloves

S39: Wear eye/face protection

Longfloor Binder Material Safety Data Sheet

2.3 Other hazards

None

3. Composition / Information on ingredients

3.1 Longfloor composition

Main Constituent	Name: Calcium Carbonate CAS: 1317-65-3 EINECS: 215-279-6
Impurities	No impurities relevant for classification and labelling
Additive (> than 1% by weight)	EC Number 204-781-0 CAS: 126-30-7

Longfloor also contains other complex non-hazardous compounds which are all less than 1% by weight.

4. First-aid measures

4.1 General advice

- **Following eye contact** | Do not rub eyes. Remove any contact lenses and flush eye(s) immediately by thoroughly rinsing with clean water. In case of irritation seek medical advice.
- **Following inhalation** | Bring to fresh air, dust in throat and nasal passages should clean. In case of serious exposure seek medical advice
- **Following Ingestion** | Wash out mouth with clean water. In case of discomfort, seek medical advice.
- **Following Skin Contact** | Wash off with plenty of water

5. Fire-fighting measures

5.1 Suitable extinguishing media

The product is not flammable and not combustible. Use extinguishing measures that are approach to local circumstances and the surrounding environment E.g. carbon dioxide, dry powder, foam, or water.

5.2 Fire-fighting equipment

No need for specialist protective equipment for fire fighters

5.3 Combustion products

Above 825°C Carbon dioxide (CO) evolution



Longfloor Binder Material Safety Data Sheet

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Wear protective equipment as described under Heading 8 and follow the advice for safe handling and use given under Heading 7. Emergency procedures are not required.

6.2 Environmental precautions

Avoid release into sewerage system

6.3 Methods and material for containment and cleaning up

Recover the spillage in a dry state if possible

Avoid dust formation

Sweep and shovel material into suitable containers for disposal before disposal as described under Heading 13.

6.4 Reference to other sections

For more information on exposure controls/personal protection or disposal considerations, please check section 8 and 13 and the Appendix of this safety data sheet.

7. Handling and storage

7.1 Bulk storage to be in a purpose built silo

Carrying limestone bags may cause sprains and strains to the back, arms, shoulders and legs. Handle with care and use appropriate control measures. Avoid generation of dust.

For limestone powders used in open ended mixers:

- Keep the height of the fall low. Start the mixing smoothly. Do not compress empty bags (dust expulsion) except when contained in another clean bag.
- To clean up limestone powder, see heading 6.3

7.2 Conditions for safe storage, including any incompatibilities

Storage in a dry, well ventilated area. Keep containers tightly closed. Do not store near acids. Bagged product should be stacked in a stable manner.

7.3 Specific end use(s)

No information available

8.1 Exposure Limit Values

Workplace exposure limits (WEL). 8hr time weighted average (TWA) values:

Dust, total inhalable: WEL 10mg/m³ 8h TWA

Dust, respirable: WEL 4mg/m³ 8h TWA



Longfloor Binder Material Safety Data Sheet

8.2 Exposure Controls

8.2.1 Appropriate engineering controls

Local mechanical exhaust ventilation

8.2.2 Individual protection measures, such as personal protective equipment

8.2.2.1 Eye/face protection. Protection is recommended. Wear approved glasses or safety goggles according to EN 166 to prevent contact with eyes.

8.2.2.2 Skin protection. Long-sleeved protective clothing is recommended when working with powders and granules.

8.2.2.3 Hand protection. The use of gloves is recommended for handling aggregates, granules and powders.

8.2.2.4 Respiratory protection. Dust masks should be used when handling powder or granular material. Suitable respiratory protection should be worn to ensure that personal exposure is less than the WEL.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

	Longfloor
Physical form	Powder/granules/chippings
Colour	Grey white / white
Odour	Odourless
pH (Saturated solution)	8.5-9.5
Boiling range/point	Not applicable
Melting point	Above 825°C
Decomposition Temperature	Above 825°C
Flash Point (PMCC)	Not applicable
Auto-flammability	Not auto-flammable
Flammability	Non-flammable
Explosive Properties	Stable under normal conditions
Vapour Pressure	Negligible vapour pressure at ambient conditions
Relative Density	26-2.8 g/cm ³
Solubility in water	0.014 g/l (20°C) 0.018 g/l (75°C)

Longfloor Binder Material Safety Data Sheet

10. Stability and reactivity

10.1 Reactivity

Acids, Limestone (calcium carbonate) reacts to form carbon dioxide (CO₂)

10.2 Chemical Stability

Under normal conditions of use and storage, Longfloor is stable

10.3 Possibility of hazardous reactions

Limestone (calcium carbonate) reacts with acids and acidic salts to generate gaseous carbon dioxide with effervescence (bubbling). The reaction with concentrated solutions of acids is rapid and exothermic. The effervescence can create extensive foaming. Ignites on contact with fluorine.

10.4 Incompatible Materials

Incompatible with acids, alum, ammonium salts, fluorine, magnesium

10.5 Hazardous Decomposition Products

Carbon Dioxide (CO₂) - oxygen displacement

11. Toxicological Information

- Acute toxicity: LD50/oral/rat = > 5000mg/kg. Not classified as harmful if swallowed.
- Local effects: mild irritation of eyes
- Chronic toxicity - carcinogenic mutagenic: no known effects

12. Ecological Information

12.1 Toxicity

Limestone is a natural mineral of the earth and in a dissolved state, the substance(s) are natural and indispensable components of natural waters. Therefore, unfavourable effects to the environment may be excluded.

Concentrated suspensions of limestone in natural waters may have an unfavourable effect on water organisms (disturbance of the microflora and fauna in the sediment and the subsequent existence of higher water organisms).

12.2 Persistence and Degradability

Calcium carbonate cannot biodegrade

Longfloor Binder Material Safety Data Sheet

10.4 Incompatible Materials

Incompatible with acids, alum, ammonium salts, fluorine, magnesium

10.5 Hazardous Decomposition Products

Carbon Dioxide (CO₂) - oxygen displacement

11. Toxicological Information

- Acute toxicity: LD50/oral/rat = > 5000mg/kg. Not classified as harmful if swallowed.
- Local effects: mild irritation of eyes
- Chronic toxicity - carcinogenic mutagenic: no known effects

12. Ecological Information

12.1 Toxicity

Limestone is a natural mineral of the earth and in a dissolved state, the substance(s) are natural and indispensable components of natural waters. Therefore, unfavourable effects to the environment may be excluded.

Concentrated suspensions of limestone in natural waters may have an unfavourable effect on water organisms (disturbance of the microflora and fauna in the sediment and the subsequent existence of higher water organisms).

12.2 Persistence and Degradability

Calcium carbonate cannot biodegrade

12.3 Bio-accumulative potential

Calcium carbonate is not a candidate for bioaccumulation in aquatic species

12.4 Mobility

Limestone is not volatile but might become airborne during handling operations

12.5 Results of PBT and vPvB assessment

Not relevant for inorganic substances. According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfil the criteria for PBT (Persistent/bio accumulative/toxic) and vPvB (very persistent/very bio accumulative). Self-classification

12.6 Other adverse effects

No other adverse effects are identified

13. Disposal considerations

Dispose of substance in suitable containers in accordance with local, regional, national, or international regulations. Do not dispose in waterways.



Longfloor Binder Material Safety Data Sheet

14. Transport Information

Calcium carbonate is not classified as hazardous for transport ADR (Road), RID (Rail), IMDG/GGVSea (Sea), ICAO/IATA (Air).

14.1 UN No	Not Applicable
14.2 UN Proper Shipping Name	Not Applicable
14.3 Transport Hazard Classes	Not Applicable
14.4. Parking Group	Not Applicable
14.5 Environmental Hazards	Not Applicable
14.6 Special Precautions for User	Not Applicable
14.7 Transport in Bulk	Not Applicable

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance

Authorisations	Not Required
Restrictions on use	None
Other EU Regulations	Calcium carbonate is not a SEVESO substance, not an ozone-depleting substance and not a persistent organic pollutant
National Regulations	Health and Safety at Work Act 1974 HSE Guidance Note EH40 (Workplace Exposure Limits) COSHH Regulations 2002 Environmental protection act 1990 Manual Handling Operations Regulations

16. Other Information

This safety data sheet is fully revised according to the CLP and REACH regulations. This safety data sheet supersedes all previous issues. Data are based on our latest knowledge but do not constitute a guarantee for any specific product features and do not establish a legally valid contractual relationship.



Longfloor Binder Material Safety Data Sheet

16.1 Abbreviations

EC50	Median effective concentration
LC50	Median lethal concentration
LD50	Median lethal dose
NOEC	No observable effect concentration
OEL	Occupational exposure limit
PBT	Persistent, bio accumulative, toxic chemical
PNEC	Predicted no-effect concentration
SCOEL	Scientific Committee on occupational exposure limits
STEL	Short-term exposure limit
TWA	Time weighted average
vPvB	Very persistent, very bio accumulative chemical

16.2 Revision

This safety data sheet is fully revised according to the CLP and REACH regulations (EC) and this version supersedes all previous issues

Disclaimer

This safety data sheet (SDS) is based on the legal provisions of the REACH Regulation (EC 1907/2006; article 31 and Annex II), as amended. Its contents are intended as a guide to the appropriate precautionary handling of the material. It is the responsibility of recipients of this SDS to ensure that the information contained therein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. Information and instructions provided in this SDS are based on the current state of scientific and technical knowledge at the date of issue indicated. It should not be construed as any guarantee of technical performance, suitability for particular applications, and does not establish a legally valid contractual relationship. This version of the SDS supersedes all previous versions

Append IX: Exposure Scenarios

Available on request from the supplier