Landscape House, Premier Way, Lowfields Business Park, Elland HX5 9HT Tel: 01422 312000 T: 01422 312000 E: grouptechnicalservices@marshalls.co.uk W: www.marshalls.co.uk/commercial

Date Created: 07/01/25

## Self-Levelling Paving Pedestal













ML3 35-50mm

ML4 50-80 mm

ML 5 80-130 mm

ML6 130-230 mm

Marshalls self-levelling pedestals provide our most flexible means of creating a floating floor system on balconies and roof decks. The heads incorporate a gimbal mechanism which allows a rotational tilt of up to 5° (or 10%). This can compensate for falls in the subgrade, or alternatively create a slight fall on the paved surface to direct surface water to the joints.

Like our Fixed Head pedestals, integral spacers create a 4mm joint between paving units and the height can be easily adjusted using the threaded core

Marshalls pedestals are recommended for use on roof decks with no vehicular access but have been tested and proven to withstand loads over one tonne.

## DESCRIPTION

Base Raw Material

PP Polypropylene











Landscape House, Premier Way, Lowfields Business Park, Elland HX5 9HT Tel: 01422 312000 T: 01422 312000 E: grouptechnicalservices@marshalls.co.uk W: www.marshalls.co.uk/commercial

Date Created: 07/01/25

## Self-Levelling Paving Pedestal

PHYSICAL PROPERTIES	
Head Diameter (mm)	120
Base Diameter (mm)	200
Spacer tab thickness	4mm
SPECIFICATION	
Reaction to fire	Polypropylene is a combustible material
Working Temperature	-40°C – 120°C
Compression (kg)	2100
SUPPLY	
Units Per Pack	25

FURTHER INFORMATION	
Cleaning & Maintenance	Cleaning & maintenance details are available on request. Resistant to moulds, algae, alkali, bitumen
Contact Us	For technical information on the design, specification and construction when utilising the product, contact the Technical Advisory Services Department on 01422 312000







