Sealed Cover Slab

Marshalls
Civils & Drainage



After an extensive research programme, Marshalls were the first to introduce the 1200mm Sealed Manhole system to the UK in 2009 to meet the challenges of modern-day construction. Since then, it has gone from strength to strength. Available in 1200, 1500 and 1800mm, the Sealed Manhole comprises of a monolithic precast concrete base (available pre-benched in any configuration), a sealed chamber ring (with a thicker wall than a standard ring), a rubber joint (so no tokstrip of similar product is required) and a sealed cover slab which is supplied with your required access. The system can be installed in as little as 30 minutes with reduced need to work in confined space, making safe site practice a real winner. It eliminates the need for wet trades resulting in rapid construction compared to traditional methods as well as a reduction in the time the excavation is open.

DESCRIPTION	
Manufacturing process	Semi dry pressed and vibrated concrete
Base raw material	DC4 Concrete
Governing manufacturing standards	BS EN 1917:2002 and BS5911-3:2022
CE marking / DOP	https://dop.marshalls.co.uk/dop/

Landscape House, Premier Way,
Lowfields Business Park,
Elland HX5 9HT
Tel: 03704 11 22 33

T: 01422 312000
F: 01422 312943
E: grouptechnicalservices@marshalls.co.uk
W: www.marshalls.co.uk/commercial

Date Created: 14/04/26

Sealed Cover Slab

Marshalls
Civils & Drainage

MATERIAL DETAILS	
Water absorption (%)	Not exceeding 6% by mass
Water Tightness	Meets the requirements of the standard
Material density	2300kg/m³ (typically)
Emission of abbestos	No content
Reaction to fire	Class A1 see European Comission Decision 2000/605/EC

SUSTAINABILITY	
Carbon footprint	Available upon request
Design life	Service life of over 120 years

ACCESSORIES	
Sealed chamber ring	Available to fit each Sealed Cover Slab
Manhole safety cover	Available to suit access aperture
Seating ring	Available to suit access aperture

FURTHER INFORMATION	
Product evolution	Marshalls reserve the right to amend the techical information as deemed necessary and in accordance with the relevant national and international standards without notice. The evolution of new product design is continuous and information is subject to change without notice. Customers should check with the supplier to ensure thatthey have the latest detail.
Contact us	For technical information on the design, specification and construction when utilising the product, contact Group Technical Servcies on 0370 411 2233

PHYSICAL PROPERTIES	STANDARD ACCESS SIZE (MM)	DIAMETER (MM)	DEPTH (MM)	WEIGHT (KG)
SCS1260	600 x 600	1200	150	615
SCS1267	675 x 675	1200	150	600
SCS151267	1200 x 675	1500	150	960
SCS1560	600 x 600	1500	150	1170
SCS1567	675 x 675	1500	150	1120
SCS1860	600 x 600	1800	175	1590
SCS1867	675 x 675	1800	175	1590
SRCS151267DS	1200 x 675	1800	175	960

Landscape House, Premier Way,
Lowfields Business Park,
Elland HX5 9HT
Tel: 03704 11 22 33

T: 01422 312000
F: 01422 312943
E: grouptechnicalservices@marshalls.co.uk
W: www.marshalls.co.uk/commercial

Date Created: 14/04/26